

## FICHA TÉCNICA DE PRODUCTO

### PLANCHA D25 (TIPO V)

Roycle S.L. B41286212  
P.I. La Red, c/ Once 1  
Alcalá de Guadaíra CP: 41500  
Tfn: 954 10 04 61 Fax: 954 10 04 62 roycle@roycle.com



DIMENSIONES (mm)	TIPO	ESPESOR	RESISTENCIA TÉRMICA	UDS/PAQ	NORMATIVA	
LARGO: 2000 ANCHO: 1000-1200	V	10	0,30	m <sup>2</sup> K/W	60	UNE-EN 13163:2013+A2:2017
		20	0,60		30	
		30	0,90		20	
		40	1,20		15	
		50	1,50		12	
		60	1,80		10	
		70	2,10		8	
		80	2,40		7	
		90	2,70		7	
		100	3,00		6	

Reaccion al Fuego <b>UNE EN 13501-1:2010</b>	Euroclases	E
Conductividad térmica <b>UNE EN 12667-2002</b>	W/m*K	0,033
Codigo de tolerancias dimensionales <b>UNE EN 13163:2013+A2</b>	T(2) - L(3) - W(3) - S(5) - P(10)	
Estabilidad dimensional <b>UNE EN 13163:2013+A2</b>	DS(N)5 - DS(70,90)	
Resistencia a flexión <b>UNE EN 12089:2013</b>	kPa	≥ 250
Resistencia a compresión 10% de deformación <b>UNE EN 826:2013</b>	kPa	≥ 140

