

FICHA TÉCNICA DE PRODUCTO

PLANCHA D30 (TIPO VI)

Roycle S.L. B41286212
P.I. La Red, c/ Once 1
Alcalá de Guadaíra CP: 41500
Tfn: 954 10 04 61 Fax: 954 10 04 62 roycle@roycle.com



DIMENSIONES (mm)	TIPO	ESPESOR	RESISTENCIA TÉRMICA	UDS/PAQ	NORMATIVA	
LARGO: 2000 ANCHO: 1000-1200	VI	10	0,30	m ² K/W	60	UNE-EN 13163:2013+A2:2017
		20	0,60		30	
		30	0,90		20	
		40	1,25		15	
		50	1,55		12	
		60	1,85		10	
		70	2,15		8	
		80	2,50		7	
		90	2,80		7	
		100	3,10		6	

Reaccion al Fuego UNE EN 13501-1:2010	Euroclases	E
Conductividad térmica UNE EN 12667-2002	W/m*K	0,032
Codigo de tolerancias dimensionales UNE EN 13163:2013+A2	T(2) - L(3) - W(3) - S(5) - P(10)	
Estabilidad dimensional UNE EN 13163:2013+A2	DS(N)5 - DS(70,90)	
Resistencia a flexión UNE EN 12089:2013	kPa	≥ 290
Resistencia a compresión 10% de deformación UNE EN 826:2013	kPa	≥ 170

